

# ***NISSEN ENVIROSAFE<sup>®</sup>*** ***INDOOR SOFTBACK MATS & PADS***

## — TECHNICAL SPECIFICATIONS —

---

<b>PAD SHAPE/SIZE:</b>	Flat, rectangular pads in varying lengths and widths
<b>CUSHIONING MATERIAL:</b>	2" EnviroSafe <sup>®</sup> foam – Medium-Firm 1 3/8" EnviroSafe <sup>®</sup> foam – Extra-Firm 2 1/2" EnviroSafe <sup>®</sup> foam – Combination Extra-Firm/Classic (IFD-50) 2" Flex-Firm (IFD-100)*
<b>ENVIROSAFE FOAM DETAILS:</b>	<ul style="list-style-type: none"><li>• Made in the USA</li><li>• Latex-free</li><li>• Toxin-free</li><li>• 100% recyclable</li><li>• Hypo allergenic</li></ul>
<b>COVERING:</b>	PVC fire-retardant, phthalate-free fabric Weight: 18 oz Tear strength*: 90 x 65 Resistant to rot, mildew and UV light  <b>Colors:</b> Green, Royal Blue, Red, Gray, Kelly Green, Maroon, Navy Blue, Black, Purple, Orange, Carolina Blue, Yellow, Sky Blue, Tan, White
<b>WARRANTY:</b>	1 year (against defects in fabric and manufacturing, prorated)
<b>ATTACHMENT OPTIONS:</b>	Velcro on 2 sides, 4 sides or none Optional PowerRail mounting system (pads)
<b>STYLE OPTIONS:</b>	Folding and non-folding options available

*\*Flex-Firm is not a part of the EnviroSafe<sup>®</sup> Product Line*

---

# ***NISSEN ENVIROSAFE®***

## ***INDOOR WOODBACK WALL PADS***

### — TECHNICAL SPECIFICATIONS —

---

<b>PAD SHAPE/SIZE:</b>	Flat, rectangular pads, custom height and width
<b>CUSHIONING MATERIAL:</b>	2" EnviroSafe® Medium-Firm 2" EnviroSafe® E-84 Class A fire-retardant 1.5" EnviroSafe® Extra-Firm
<b>BACKER:</b>	7/16" urea formaldehyde-free OSB (oriented strand board)
<b>COVERING:</b>	PVC fire-retardant, phthalate-free fabric Weight: 18 oz    Tear strength*: 90 x 65 Resistant to rot, mildew and UV light  <b>Flammability**:</b> meets NFPA 701, CA Fire Marshal, UL 300 standards <b>Colors:</b> Green, Royal Blue, Red, Gray, Kelly Green, Maroon, Navy Blue, Black, Purple, Orange, Carolina Blue, Yellow, Sky Blue, Tan, White
<b>FLAMMABILITY*:</b>	Calif Technical Bulletin #117, ASTM E-84-08a
<b>ASTM SPECS*:</b>	Meets ASTM F-2440 for impact resistance (Medium-Firm/Bonded type), ASTM E-84-08a for Class A FR, ASTM D2261 for tear strength
<b>WARRANTY:</b>	1 year (against defects in fabric and manufacturing, prorated)
<b>ATTACHMENT OPTIONS:</b>	1" nail margins (lips) for screwing pads into wall Z-clips for mounting pads to wall

---